
Round edge profiles (open)

- Information Sheet -









APPLICATION:

Dural's DURABORD round edge profiles have been developed to provide a smooth fit at outer corners with walls. They are gently rounded, Apart from their protective function, they are also suitable for sophisticated designs. In addition, they are suitable for covering wall sockets for use with tiles, carpet, parquet or natural stone. High-quality shaped pieces are used to connect profiles




DURABORD is available in the following versions: standard PVC and high gloss-painted ("Star" with protective peel-off strip). Available in a variety of single colours, various marble and granite tones.


PROPERTIES:

DURABORD PVC profiles are especially designed for decorative effect. They are made of imbued PVC and are highly UV-stable. Colours may nevertheless fade over time when used in external locations, (e.g. in bright sunlight). DURABORD PVC profiles are not suitable for corners and edges subject to large amounts of wear.

N.B.: The use of coloured mortar with ultra fine colour pigments in conjunction with plastic profiles may result in permanent staining of the profiles. We recommend taking appropriate protective measures as a precaution.

For all products and materials, the following applies: The suitability of the material with regard to the expected mechanical loading and chemical exposure must be investigated carefully in each individual case. The generally recognised rules of good engineering practice must always be observed!





DURAL GmbH

Südring 11 D-56412 Ruppach-Goldhausen Tel. +49 (0) 2602/9261-0 Fax +49 (0) 2602/9261-50 info@dural.com

DURABORD

Round edge profiles (open) **PVC**

- Information Sheet -

DURAL

INSTALLATION:

- 1. DURABORD round edge profiles should be selected according to the tile thickness.
- 2. Tile adhesive should be applied to the edges with a toothed trowel. For outer edges at walls first ensure that the wall is fully tiled.
- 3. Press the DURABORD profiles into the adhesive bedding and align them.
- 4. Securing brackets should be completely covered over with adhesive.
- 5. Firmly press in the tiles and align them so that they are flush with the upper edge of the profile. Lay tiles so that they are fully tessellated.
- 6. Allow a 2-3 mm gap around the profile.
- 7. Completely fill the gap between tiles and profile with grout.

MAINTENANCE:

DURABORD profiles do not require any special maintenance. Deposits of dirt can be removed using ordinary cleaning materials. Cleaning materials may not contain hydrochloric or hydrofluoric acid (solvents are also to be avoided with PVC) and may not cause abrasion.

PRODUCT DATA:

MATERIAL:	– PVC standard or PVC high gloss ("Star" with peel-off strip)
COLOURS:	 white, jasmine, beige, black, brown, pergamon light, grey, blue, ivory, bright red, whisper blue, whisper pink, pergamon, silver grey, mint, peach, royal blue, bright yellow, dark green. marble white, marble beige, marble grey, marble black, marble pink, marble green. granite white, granite beige, granite grey, granite black
LENGTH:	250 cm
HEIGHT:	6 / 8 / 10 / 12,5 mm
ACCESSORIES:	External corners X or Y

DURAL GmbH

Südring 11 D-56412 Ruppach-Goldhausen Tel. +49 (0) 2602/9261-0 Fax +49 (0) 2602/9261-50 info@dural.com